

DONOHUE HEATING SERVICES

ELECTRIC RADIATOR DATA SHEETS

DELIVERY
CODE
A

THIS ITEM NORMALLY
DISPATCHED WITHIN
48 HOURS OF ORDER

- Standard rails 22mm tube diameter
- Available as straight or curved
- Sparkling highly polished chrome finish
- Supplied complete with fixing kit, including plugs and vents
- Manufactured under BS EN ISO 9001 quality standards
- Pressure tested to 10 bar / maximum working pressure 7 bar
- Insulation class 1
- ON/OFF – IP 55 rated
Thermostatically Adjustable – IPX4 rated
- Element is complete with 1.5m fly-lead
- Recommended installation is carried out by a qualified electrician

Plan profiles:



ON/OFF element type. Inset; Thermostatically Adjustable element type.



Height: 800mm

Tube diameter: 22mm
Width: 400, 500, 600mm
No. of Crossrails: 14
Style: Straight, Curved
Finish: Chrome



Height: 1000mm

Tube diameter: 22mm
Width: 400, 500, 600mm
No. of Crossrails: 16
Style: Straight, Curved
Finish: Chrome



Height: 1200mm

Tube diameter: 22mm
Width: 400, 500, 600mm
No. of Crossrails: 20
Style: Straight, Curved
Finish: Chrome

Ø 22mm Chrome

Width (mm)	Height (mm)	C/C Tappings (mm)	Quantity of Cross Rails	Tube Ø (mm)	Element Type
500	800	405	14	Ø22	ON/OFF*
500	1000	405	16	Ø22	ON/OFF*
500	1200	455	20	Ø22	ON/OFF*
600	1200	555	20	Ø22	ON/OFF*
500	800	405	14	Ø22	Thermostatic/Adjustable
500	1000	405	16	Ø22	Thermostatic/Adjustable
500	1200	455	20	Ø22	Thermostatic/Adjustable
600	1200	555	20	Ø22	Thermostatic/Adjustable

STRAIGHT

Code	Heating Element Power (W)	Delivery Code
ESTR508C	150	A
ESTR510C	200	A
ESTR512C	300	A
ESTR612C	400	A
ETSTR508C	150	A
ETSTR510C	150	A
ETSTR512C	300	A
ETSTR612C	600	A

CURVED

Code	Heating Element Power (W)	Delivery Code
ECTR508C	150	A
ECTR510C	200	A
ECTR512C	300	A
ECTR612C	400	A
ETCTR508C	150	A
ETCTR510C	150	A
ETCTR512C	300	A
ETCTR612C	600	A

Notes: • Chemical Mixture – Monoethilen Glycol • C/C Tappings = Distance between tapping centre * Element complete with thermostatic cut-out
Wall to C/C tappings; Straight = 64-86mm adjustable. Curved = 52-74mm adjustable.