

DONOHUE HEATING SERVICES

TOWEL RANGE DATA SHEETS

MODERN
CONTEMPORARY
DESIGN

DELIVERY
CODE
A

THIS ITEM NORMALLY
DISPATCHED WITHIN
48 HOURS OF ORDER



**EXTENDED RANGE
300mm & WHITE RAILS**



Height: 800mm

Tube diameter: 22mm
Width: 400, 500, 600mm
No. of Crossrails: 14
Style: Straight, Curved
Finish: Chrome

Height: 1000mm

Tube diameter: 22mm
Width: 400, 500, 600mm
No. of Crossrails: 16
Style: Straight, Curved
Finish: Chrome



Height: 1200mm

Tube diameter: 22mm
Width: 400, 500, 600mm
No. of Crossrails: 20
Style: Straight, Curved
Finish: Chrome

Height: 1600mm

Tube diameter: 22mm
Width: 400, 500, 600mm
No. of Crossrails: 26
Style: Straight, Curved
Finish: Chrome



Height: 1800mm


Tube diameter: 22mm
Width: 500, 600mm
No. of Crossrails: 31
Style: Straight, Curved
Finish: Chrome

Product Features

SIZES	MATERIAL	COLOUR	PRESSURE TESTED TO	GUARANTEE
28	S	CHR	10 BAR	5 YEARS

K RAILS

Standard Product Range



- Standard rails 22mm tube diameter
- Available as straight or curved
- Sparkling highly polished chrome finish or a classic brilliant ice white
- Supplied complete with fixing kit, including plugs and vents
- Manufactured under BS EN ISO 9001 quality standards
- Pressure tested to 10 bar / maximum working pressure 7 bar

Ø 25mm Straight						
Width (mm)	Height (mm)	C/C Tappings (mm)	Headers Dimensions (mm)	Quantity of Cross Rails	Tube Ø (mm)	Summer Element Watts
300	800	255	30/40/1.5	14	Ø22	300
300	1000	255	30/40/1.5	16	Ø22	300
300	1200	255	30/40/1.5	20	Ø22	300
300	1600	255	30/40/1.5	26	Ø22	500
400	800	355	30/40/1.5	14	Ø22	300
400	1000	355	30/40/1.5	16	Ø22	300
400	1200	355	30/40/1.5	20	Ø22	500
400	1600	355	30/40/1.5	26	Ø22	500
500	800	455	30/40/1.5	14	Ø22	300
500	1000	455	30/40/1.5	16	Ø22	300
500	1200	455	30/40/1.5	20	Ø22	500
500	1600	455	30/40/1.5	26	Ø22	500
500	1800	455	30/40/1.5	31	Ø22	500
600	800	555	30/40/1.5	14	Ø22	300
600	1000	555	30/40/1.5	16	Ø22	300
600	1200	555	30/40/1.5	20	Ø22	500
600	1600	555	30/40/1.5	26	Ø22	500
600	1800	555	30/40/1.5	31	Ø22	800

Ø 22mm Curved						
Width (mm)	Height (mm)	C/C Tappings (mm)	Headers Dimensions (mm)	Quantity of Cross Rails	Tube Ø (mm)	Summer Element Watts
300	800	255	30/40/1.5	14	Ø22	300
300	1000	255	30/40/1.5	16	Ø22	300
300	1200	255	30/40/1.5	20	Ø22	300
300	1600	255	30/40/1.5	26	Ø22	500
400	800	355	30/40/1.5	14	Ø22	300
400	1000	355	30/40/1.5	16	Ø22	300
400	1200	355	30/40/1.5	20	Ø22	500
400	1600	355	30/40/1.5	26	Ø22	500
500	800	455	30/40/1.5	14	Ø22	300
500	1000	455	30/40/1.5	16	Ø22	300
500	1200	455	30/40/1.5	20	Ø22	500
500	1600	455	30/40/1.5	26	Ø22	500
500	1800	455	30/40/1.5	31	Ø22	500
600	800	555	30/40/1.5	14	Ø22	300
600	1000	555	30/40/1.5	16	Ø22	300
600	1200	555	30/40/1.5	20	Ø22	500
600	1600	555	30/40/1.5	26	Ø22	500
600	1800	555	30/40/1.5	31	Ø22	800

CHROME			
Output ΔT50°C			
Code	Watts	BTUs	Delivery Code
STR308C	222	757	A
STR310C	264	902	A
STR312C	322	1,098	A
STR316C	425	1,452	A
STR408C	255	870	A
STR410C	304	1,037	A
STR412C	370	1,262	A
STR416C	489	1,668	A
STR508C	302	1,030	A
STR510C	357	1,218	A
STR512C	436	1,488	A
STR516C	576	1,965	A
STR518C	662	2,259	A
STR608C	350	1,194	A
STR610C	413	1,409	A
STR612C	506	1,726	A
STR616C	668	2,279	A
STR618C	768	2,620	A

CHROME			
Output ΔT50°C			
Code	Watts	BTUs	Delivery Code
CTR308C	222	757	A
CTR310C	264	902	A
CTR312C	322	1,098	A
CTR316C	425	1,452	A
CTR408C	255	870	A
CTR410C	304	1,037	A
CTR412C	370	1,262	A
CTR416C	489	1,668	A
CTR508C	302	1,030	A
CTR510C	357	1,218	A
CTR512C	436	1,488	A
CTR516C	576	1,965	A
CTR518C	662	2,259	A
CTR608C	350	1,194	A
CTR610C	413	1,409	A
CTR612C	506	1,726	A
CTR616C	668	2,279	A
CTR618C	768	2,620	A

WHITE			
Output ΔT50°C			
Code	Watts	BTUs	Delivery Code
STR308W	316	1,079	A
STR310W	377	1,286	A
STR312W	459	1,565	A
STR316W	606	2,068	A
STR408W	363	1,240	A
STR410W	433	1,478	A
STR412W	527	1,799	A
STR416W	697	2,378	A
STR508W	430	1,468	A
STR510W	509	1,736	A
STR512W	621	2,120	A
STR516W	821	2,801	A
STR518W	943	3,219	A
STR608W	499	1,702	A
STR610W	589	2,008	A
STR612W	721	2,460	A
STR616W	952	3,248	A
STR618W	1,094	3,734	A

WHITE			
Output ΔT50°C			
Code	Watts	BTUs	Delivery Code
CTR308W	316	1,079	A
CTR310W	377	1,286	A
CTR312W	459	1,565	A
CTR316W	606	2,068	A
CTR408W	363	1,240	A
CTR410W	433	1,478	A
CTR412W	527	1,799	A
CTR416W	697	2,378	A
CTR508W	430	1,468	A
CTR510W	509	1,736	A
CTR512W	621	2,120	A
CTR516W	821	2,801	A
CTR518W	943	3,219	A
CTR608W	499	1,702	A
CTR610W	589	2,008	A
CTR612W	721	2,460	A
CTR616W	952	3,248	A
CTR618W	1,094	3,734	A

Notes: • C/C Tappings = Distance between tapping centre • Outputs quoted are based on a mean water temperature of 70°C and a room temperature of 20°C.
Wall to C/C tappings; Straight = 64-86mm adjustable. Curved = 52-74mm adjustable.